## Certificate of Weight Calibration

ISO/IEC 17025:2017 & ANSI/NCSL-Z540-1-1994 ACCREDITED

			15	ISO/IEC 17025:2017 & ANSI/NCSL-2540-1-1994 ACCREDITED							
Traceable Certificate Number:											
Contractor:		ADVANCED SCALE INC				the Nati	onal Institute				
		13 DELTA DR UNIT 6			1	.dl u.	Sel.				
		LONDONDERRY, NH 03053									
<b>_</b> . <b>_</b>					5	$/$ $\Lambda$					
Purchase Order Number: Client:		10349			<i>ا چ</i>						
		ADVANCED SCALE INC			8						
		13 DELTA DR UNIT 6			eable to the SI the						
		LONDONDERRY, NH 03053			lace		and the second s				
Date Received:	:	06 Mar 2024			1	8					
Date Calibrated:07 Mar 2024 to 12 Mar 2024Recalibration Date:28 Feb 2025NIST Certificate Number:684/O-0000046697If there are two NIST numbers, one or both may applyCalibrated By:17Procedure:W105-0095 Rev. DCondition of Weights:Acceptable for Calibration		07 Mar 2024 to 12 Mar 2024				LAKEN	EIGHING SYSTE				
		28 Feb 2025				- 10	EIGHING				
		684/O-0000046697									
		17									
		WI05-0095 Rev. D									
		Acceptable for Calibration									
Description of	Weights:	200 g to 5 kg Polished Weights, ASTM Class 1,	S/N 07	7734							
Comments:					-						
	A.	Key Notes		A _		eaning Lo	evels				
Finish	<u> </u>	eight does not meet the finish requirements			Ousted with brush or clot						
Material	Indicates the we	veight does not meet the material requirements			B Spot cleaned with ethyl alcohol						
New Wt	<ul> <li>Indicates new weight</li> <li>Indicates replaced missing weight with new weight</li> </ul>				Il surface cleaned with ethyl alcohol						
Missing Wt				<ul> <li>D Spot cleaned with non-alcohol solvent followed by ethyl alcohol</li> <li>E Full surface cleaned with non-alcohol solvent followed by ethyl alcohol</li> </ul>							
Damaged Wt 🔀 Indicates replac		ed damaged weight		E Full surface cleaned with non-alcohol solvent followed by ethyl alcoho     F No cleaning performed							
		ed out of tolerance weight	i i	Material Abbreviations							
оот		ction plus or minus Uncertainty greater than or equal to MF	E /	AL	Aluminum	TA	Tantalum				
Magnetic Wt	★★Indicates replace			SS	Stainless Steel	BR	Brass				
Design	Indicates the we	eight does not meet the design or shape requirements	(	CI	Cast Iron	PL	Platinum				
Repainted	Indicates the we	eight was repainted after As Found obtained	I	IR	Iron	NS	Nickel Silver				
•	4		ſ	MS	Mild Steel	OR	Other/Unknown				
Other The See comments		above									

Check with your local state agency for certification of compliance on Legal-for-Trade items. The weight accuracy class is referenced in the Description of Weights. Unless otherwise noted, the weights calibrated meet the requirements of the accuracy class. Results relate only to weights calibrated. The Surface Finishes of weights are evaluated visually. Weights are screened for magnetism using work instruction WI05-0035 when they are new, when requested by the customer or when weights are suspected of not meeting specifications. Density if measured using OIML R111-1 (2004) method A2. Conventional Mass is reported based on a reference density of 8.0 g/cm<sup>3</sup>. The Uncertainty of Measurement is included in the determination of Maximum Permissible Error (MPE) Pass/Fail Criteria. The specifications for Maximum Permissible Error (MPE) can be found in NIST Handbook 105-1 (2019), NIST Handbook 105-1 (1990), ASTM E617-23 or OIML R111-1 (2004), manufacturer specifications or customer specifications.

The Uncertainty assigned to the Conventional Mass values are the result of the root-sum-square of the type A and type B components, calculated in accordance with NIST SOP 29 and the Guide to the expression of uncertainty in measurement, with coverage factor (*k*=2), to express the expanded uncertainty with an approximate 95.45% confidence level. This report is not to be used to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any government agency. **This document and all data within, shall not be reproduced, except in full, without the written approval of Rice Lake Weighing Systems**.



**RICE LAKE** 



Prepared By: **Rice Lake Weighing Systems®**●PN 64784●12/21 230 West Coleman Street●Rice Lake, WI 54868●USA TEL: 715-234-9171●FAX: 715-234-6967 Definitions: http://certs.ricelake.com/certs/DefinitionsV2.docx Page 1 of 2



Issued Date: Duplicate



## RICE LAKE Certificate of Weight Calibration

Traceable Cer Client: Date Calibrate		ADVANCE 07 Mar 20	3689134 ADVANCED SCALE INC 07 Mar 2024 to 12 Mar 2024 Left Data (As Found Data is undifferentiated from As Left I						erature Rang ure Range: ve Humidity nless listed	ge: Range:	C 17025:2017 & ANSI/NCSL-Z540-1-1994 ACCREDITED 21.52 °C to 21.71 °C 723.13 mmHg to 734.21 mmHg 49 % to 50 %					
Nominal Value	Unique ID	True Mass (Same UOM as Nom.)	True Mass Corr. (mg)	Conv. Mass	Conv. Mass Corr. (mg)	( <i>k</i> =2) Unc. (± mg)	MPE (± mg)	MPE Pass (Y=Pass N=Fail)	Assumed Density (g/cm <sup>3</sup> )	Assumed Material	Const. Type	, Balance Used	Reference Standard Set Used	Air Density (mg/cm <sup>3</sup> )	Clean Level	
200 g	07734	200.000327	0.327	200.000138	0.138	0.048	0.50	Y	7.95	SS		699Q	T535Q	1.1344	A	
300 g	07734	300.000747	0.747	300.000464	0.464	0.065	0.75	Y	7.95	SS	П	699Q	T535Q	1.1344	Α	
500 g	07734	500.001027	1.027	500.000555	0.555	0.078	1.2	Y	7.95	SS	П	699Q	T535Q	1.1343	A (	
1 kg	07734.	1.00000157	1.57	1.00000062	0.62	0.15	2.5	Y	7.95	SS	II	699Q	T535Q	1.1339	A	
2 kg	07734	2.00000407	4.07	2.00000218	2.18	0.33	5.0	Y	7.95	SS	П	208Q	T535Q	1.1520	) A	
2 kg	07734.	2.00000357	3.57	2.00000169	1.69	0.33	5.0	Y	7.95	SS	П	208Q	T535Q	1.1520	) A	
5 kg	07334	5.00000749	7.49	5.00000277	2.77	0.98	12	Y	7.95	SS	П	208Q	T535Q	1.1486	βA	