RICELAKE

Certificate of Weight Calibration

ISO/IEC 17025 & ANSI/NCSL-Z540-1-1994 ACCREDITED

Traceable Certificate Number: 3615210

Contractor: ADVANCED SCALE INC

13 DELTA DR UNIT 6 LONDONDERRY, NH 03053

Purchase Order Number: 10239

Client: ADVANCED SCALE INC

13 DELTA DR UNIT 6

LONDONDERRY, NH 03053

Date Received: 26 Sep 2023

Date Calibrated: 01 Oct 2023 to 02 Oct 2023

Recalibration Date: 30 Sep 2024 **NIST Certificate Number**: 684/O-000046697

If there are two NIST numbers, one or both may apply **Calibrated By:** 17

Procedure: WI05-0095 Rev. D

Condition of Weights: Acceptable for Calibration

See comments above

Description of Weights: 100 g to 1 kg Polished Weight Set, ASTM Class 1, S/N 07735

Indicates the weight was repainted after As Found obtained

Comments:

Finish

Material

New Wt

OOT

Design

Missing Wt

Damaged Wt

Magnetic Wt

Repainted Other

Replaced OOT



Key Notes Indicates the weight does not meet the finish requirements Indicates the weight does not meet the material requirements Indicates new weight Indicates replaced missing weight with new weight Indicates replaced damaged weight Indicates replaced out of tolerance weight Indicates correction plus or minus Uncertainty greater than or equal to MPE ★ Indicates replaced magnetic weight Indicates the weight does not meet the design or shape requirements

Check with your local state agency for certification of compliance on Legal-for-Trade items. The weight accuracy class is referenced in the Description of Weights. Unless otherwise noted, the weights calibrated meet the requirements of the accuracy class. Results relate only to weights calibrated. The Surface Finishes of weights are evaluated visually. Weights are screened for magnetism using work instruction WI05-0035 when they are new, when requested by the customer or when weights are suspected of not meeting specifications. Density if measured is measured using OIML R111-1 (2004) method A2. Conventional Mass is reported based on a reference density of 8.0 g/cm³. The Uncertainty of Measurement is included in the determination of Maximum Permissible Error (MPE) Pass/Fail Criteria. The specifications for Maximum Permissible Error (MPE) can be found in NIST Handbook 105-1 (2019), NIST Handbook 105-1 (1990), ASTM E617-18 or OIML R111-1 (2004), manufacturer specifications or customer specifications.

The Uncertainty assigned to the Conventional Mass values are the result of the root-sum-square of the type A and type B components, calculated in accordance with NIST SOP 29 and the Guide to the expression of uncertainty in measurement, with coverage factor (k=2), to express the expanded uncertainty with an approximate 95.45% confidence level. This report is not to be used to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any government agency. **This document and all data within, shall not be reproduced, except in full, without the written approval of Rice Lake Weighing Systems**.

Cleaning Levels

- A Dusted with brush or cloth
- B Spot cleaned with ethyl alcohol
- C Full surface cleaned with ethyl alcohol
- D Spot cleaned with non-alcohol solvent followed by ethyl alcohol
- E Full surface cleaned with non-alcohol solvent followed by ethyl alcohol
- F No cleaning performed

Material Abbreviations

AL	Aluminum	IA	Tantalum
SS	Stainless Steel	BR	Brass
CI	Cast Iron	PL	Platinum
IR	Iron	NS	Nickel Silver
MS	Mild Steel	OR	Other/Unknown

Dan Demers, Metrologist



Prepared By:


Rice Lake Weighing Systems®●PN 64784●12/21 230 West Coleman Street●Rice Lake, WI 54868●USA

TEL: 715-234-9171 ● FAX: 715-234-6967

 ${\color{blue} \textbf{Definitions:}} \ \underline{\textbf{http://certs.ricelake.com/certs/DefinitionsV2.docx}}$

Page 1 of 2







RICE LAKE

Certificate of Weight Calibration

ISO/IEC 17025 & ANSI/NCSL-Z540-1-1994 ACCREDITED

21.56 °C to 21.68 °C

Traceable Certificate Number: 3615210 Temperature Range:

Client: ADVANCED SCALE INC Pressure Range: 733.49 mmHg to 734.24 mmHg

Date Calibrated: 01 Oct 2023 to 02 Oct 2023 Relative Humidity Range: 49 % to 54 %

As Left Data (As Found Data is undifferentiated from As Left Data unless listed in As Found Data table)															
Nominal Value	Unique ID	True Mass (Same UOM as Nom.)	True Mass Corr. (mg)	Conv. Mass (Same UOM as Nom.)	Conv. Mass Corr. (mg)	(<i>k</i> =2) Unc. (± mg)	MPE (± mg)	MPE Pass (Y=Pass N=Fail)	Assumed Density (g/cm ³)	Assumed Material	Const. Type	Balance Used	Reference Standard Set Used	Density	Clean Level
100 g	07735	100.000002	0.002	99.999907	-0.093	0.022	0.25	Υ	7.95	SS	II	2060Q	U520Q	1.1498	3 A
200 g	07735	200.000442	0.442	200.000253	0.253	0.045	0.50	Υ	7.95	SS	II	699Q	L595Q	1.1514	Α
300 g	07735.	300.000585	0.585	300.000302	0.302	0.064	0.75	Υ	7.95	SS	II	699Q	L595Q	1.1518	ίA
500 g	07735.	500.001135	1.135	500.000663	0.663	0.068	1.2	Υ	7.95	SS	II	699Q	L595Q	1.1513	, A
1 kg	07735	1.00000222	2.22	1.00000128	1.28	0.13	2.5	Υ	7.95	SS	II	699Q	L595Q	1.1519	А