RICELAKE

Certificate of Weight Calibration

ISO/IEC 17025 & ANSI/NCSL-Z540-1-1994 ACCREDITED

Traceable Certificate Number: 3596085B

Contractor: ADVANCED SCALE INC

13 DELTA DR UNIT 6 LONDONDERRY, NH 03053

Purchase Order Number: 10217

Client: ADVANCED SCALE INC

13 DELTA DR UNIT 6

LONDONDERRY, NH 03053

Date Received:22 Aug 2023Date Calibrated:28 Aug 2023Recalibration Date:28 Aug 2024NIST Certificate Number:684/292805-19If there are two NIST numbers, one or both may apply

Calibrated By: 05

Procedure: WI05-0095 Rev. D

Condition of Weights: Acceptable for Calibration

See comments above

Description of Weights: 200 g Polished Weight, ASTM Class 1, S/N 69M8 with dot

Indicates the weight does not meet the design or shape requirements

Indicates the weight was repainted after As Found obtained

Comments:

Finish

Material

New Wt

OOT

Design

Other

Missing Wt

Damaged Wt

Magnetic Wt

Repainted

Replaced OOT



Key Notes indicates the weight does not meet the finish requirements Indicates the weight does not meet the material requirements Indicates new weight Indicates replaced missing weight with new weight Indicates replaced damaged weight Indicates replaced out of tolerance weight Indicates correction plus or minus Uncertainty greater than or equal to MPE Indicates replaced magnetic weight

Check with your local state agency for certification of compliance on Legal-for-Trade items. The weight accuracy class is referenced in the Description of Weights. Unless otherwise noted, the weights calibrated meet the requirements of the accuracy class. Results relate only to weights calibrated. The Surface Finishes of weights are evaluated visually. Weights are screened for magnetism using work instruction WI05-0035 when they are new, when requested by the customer or when weights are suspected of not meeting specifications. Density if measured using OIML R111-1 (2004) method A2. Conventional Mass is reported based on a reference density of 8.0 g/cm³. The Uncertainty of Measurement is included in the determination of Maximum Permissible Error (MPE) Pass/Fail Criteria. The specifications for Maximum Permissible Error (MPE) can be found in NIST Handbook 105-1 (2019), NIST Handbook 105-1 (1990), ASTM E617-18 or OIML R111-1 (2004), manufacturer specifications or customer specifications.

The Uncertainty assigned to the Conventional Mass values are the result of the root-sum-square of the type A and type B components, calculated in accordance with NIST SOP 29 and the Guide to the expression of uncertainty in measurement, with coverage factor (k=2), to express the expanded uncertainty with an approximate 95.45% confidence level. This report is not to be used to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any government agency. **This document and all data within, shall not be reproduced, except in full, without the written approval of Rice Lake Weighing Systems**.

Cleaning Levels

- A Dusted with brush or cloth
- B Spot cleaned with ethyl alcohol
- C Full surface cleaned with ethyl alcohol
- D Spot cleaned with non-alcohol solvent followed by ethyl alcohol
- E Full surface cleaned with non-alcohol solvent followed by ethyl alcohol
- F No cleaning performed

Material Abbreviations

AL	Aluminum	TA	Tantalum
SS	Stainless Steel	BR	Brass
CI	Cast Iron	PL	Platinum
IR	Iron	NS	Nickel Silver
MS	Mild Steel	OR	Other/Unknown

Dan Demers, Metrologist



Prepared By:

Rice Lake Weighing Systems®●PN 64784●12/21 230 West Coleman Street●Rice Lake, WI 54868●USA

TEL: 715-234-9171 ● FAX: 715-234-6967

Definitions: http://certs.ricelake.com/certs/DefinitionsV2.docx

Page 1 of 2





RICE LAKE

Certificate of Weight Calibration

ISO/IEC 17025 & ANSI/NCSL-Z540-1-1994 ACCREDITED

Traceable Certificate Number: 3596085B

Temperature Range:

21.70 °C

Client: ADVANCED SCALE INC

Pressure Range: 731.33 mmHg

Date Calibrated: 28 Aug 2023 Relative Humidity Range: 50 %

As Left Data (As Found Data is undifferentiated from As Left Data unless listed in As Found Data table)															
Nominal Value	Unique ID	True Mass (Same UOM as Nom.)	True Mass Corr. (mg)	Conv. Mass (Same UOM as Nom.)	Conv. Mass Corr. (mg)	(<i>k</i> =2) Unc. (± mg)	MPE (± mg)	MPE Pass (Y=Pass N=Fail)	Assumed Density (g/cm ³)	Assumed Material	Const. Type	Balance Used	Reference Standard Set Used	Density	Clean Level
200 g	69M8.	200.000197	0.197	200.000008	0.008	0.028	0.50	Υ	7.95	SS	II	1521Q	345Q	1.1466	A

RICELAKE

Certificate of Weight Cali

ISO/IEC 17025 & ANSI/NCSL-Z540-1-1994 ACCREDITED

Traceable Certificate Number: 3596085C

Contractor: ADVANCED SCALE INC. 13 DELTA DR UNIT 6

LONDONDERRY, NH 03053

Purchase Order Number: 10217

Client: ADVANCED SCALE INC

13 DELTA DR UNIT 6

LONDONDERRY, NH 03053

Date Received: 22 Aug 2023 **Date Calibrated:** 28 Aug 2023 **Recalibration Date:** 28 Aug 2024 **NIST Certificate Number:** 684/292805-19 If there are two NIST numbers, one or both may apply

Calibrated By: 05

Procedure: WI05-0095 Rev. D **Condition of Weights:** Acceptable for Calibration

See comments above

Description of Weights: 200 g Polished Weight, ASTM Class 1, S/N 69M9 with two dots

Comments:

Finish

Material

New Wt

OOT

Design

Repainted Other



Key Notes * Indicates the weight does not meet the finish requirements Indicates the weight does not meet the material requirements Indicates new weight Missing Wt Indicates replaced missing weight with new weight Damaged Wt X Indicates replaced damaged weight ★ Indicates replaced out of tolerance weight Replaced OOT Indicates correction plus or minus Uncertainty greater than or equal to MPE Magnetic Wt ★★Indicates replaced magnetic weight Indicates the weight does not meet the design or shape requirements

Indicates the weight was repainted after As Found obtained

Check with your local state agency for certification of compliance on Legal-for-Trade items. The weight accuracy class is referenced in the Description of Weights. Unless otherwise noted, the weights calibrated meet the requirements of the accuracy class. Results relate only to weights calibrated. The Surface Finishes of weights are evaluated visually. Weights are screened for magnetism using work instruction WI05-0035 when they are new, when requested by the customer or when weights are suspected of not meeting specifications. Density if measured is measured using OIML R111-1 (2004) method A2. Conventional Mass is reported based on a reference density of 8.0 g/cm3. The Uncertainty of Measurement is included in the determination of Maximum Permissible Error (MPE) Pass/Fail Criteria. The specifications for Maximum Permissible Error (MPE) can be found in NIST Handbook 105-1 (2019), NIST Handbook 105-1 (1990), ASTM E617-18 or OIML R111-1 (2004), manufacturer specifications or customer specifications.

The Uncertainty assigned to the Conventional Mass values are the result of the root-sum-square of the type A and type B components, calculated in accordance with NIST SOP 29 and the Guide to the expression of uncertainty in measurement, with coverage factor (k=2), to express the expanded uncertainty with an approximate 95.45% confidence level. This report is not to be used to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any government agency. This document and all data within, shall not be reproduced, except in full, without the written approval of Rice Lake Weighing Systems.

Cleaning Levels

- A Dusted with brush or cloth
- Spot cleaned with ethyl alcohol
- С Full surface cleaned with ethyl alcohol
- Spot cleaned with non-alcohol solvent followed by ethyl alcohol
- Full surface cleaned with non-alcohol solvent followed by ethyl alcohol
- No cleaning performed

Material Abbreviations

AL	Aluminum	TA	Tantalum
SS	Stainless Steel	BR	Brass
CI	Cast Iron	PL	Platinum
IR	Iron	NS	Nickel Silver
MS	Mild Steel	OR	Other/Unknown



Prepared By:

Rice Lake Weighing Systems®●PN 64784●12/21 230 West Coleman Street ● Rice Lake, WI 54868 ● USA

TEL: 715-234-9171 FAX: 715-234-6967

Definitions: http://certs.ricelake.com/certs/DefinitionsV2.docx

Page 1 of 2





RICE LAKE

Certificate of Weight Calibration

Temperature Range:

Pressure Range:

ISO/IEC 17025 & ANSI/NCSL-Z540-1-1994 ACCREDITED

21.70 °C

731.33 mmHg

Traceable Certificate Number: 3596085C

Client:

3596085C ADVANCED SCALE INC

Date Calibrated: 28 Aug 2023 Relative Humidity Range: 50 %

				· · ·											
As Left Data (As Found Data is undifferentiated from As Left Data unless listed in As Found Data table)															
Nominal Value	Unique ID	True Mass (Same UOM as Nom.)	True Mass Corr. (mg)	Conv. Mass (Same UOM as Nom.)	Conv. Mass Corr. (mg)	(<i>k</i> =2) Unc. (± mg)	MPE (± mg)	MPE Pass (Y=Pass N=Fail)	Assumed Density (g/cm ³)	Assumed Material	Const. Type	Balance Used	Reference Standard Set Used	Density	Clean Level
200 a	69M9	200.000234	0.234	200.000046	0.046	0.028	0.50	Υ	7.95	SS	ll l	1521Q	345Q	1.1466	A