RICELAKE

Certificate of Weight Calib

ISO/IEC 17025 & ANSI/NCSL-Z540-1-1994 ACCREDITED

Traceable Certificate Number: 3330900A

Contractor: ADVANCED SCALE INC. 13 DELTA DR UNIT 6

LONDONDERRY, NH 03053-2372

Purchase Order Number: 9835

Client: ADVANCED SCALE INC

13 DELTA DR UNIT 6

LONDONDERRY, NH 03053-2372

Date Received: 18 Feb 2022

Date Calibrated: 22 Feb 2022 to 23 Feb 2022

Recalibration Date: 22 Feb 2023

NIST Certificate Number: 684/291344-18 & 684/292805-19

If there are two NIST numbers, one or both may apply Calibrated By: 05, 17

Procedure: WI05-0095 Rev. D **Condition of Weights:** Acceptable for Calibration

See comments above

Description of Weights: 5 mg to 100 g Polished Weights, ASTM Class 1, S/N 0M31

Indicates the weight was repainted after As Found obtained

Comments:

Finish

Material

New Wt

OOT

Design

Other

Missing Wt

Damaged Wt

Magnetic Wt

Repainted

Replaced OOT



Cleaning Levels

Spot cleaned with non-alcohol solvent followed by ethyl alcohol

E Full surface cleaned with non-alcohol solvent followed by ethyl alcohol

Material Abbreviations

TA

BR

PL

NS

Tantalum

Platinum

Nickel Silver

Brass

Key Notes * Indicates the weight does not meet the finish requirements Indicates the weight does not meet the material requirements Indicates new weight Indicates replaced missing weight with new weight X Indicates replaced damaged weight ★ Indicates replaced out of tolerance weight Indicates correction plus or minus Uncertainty greater than or equal to MPE ★★Indicates replaced magnetic weight Indicates the weight does not meet the design or shape requirements

(2019), NIST Handbook 105-1 (1990), ASTM E617-18 or OIML R111-1 (2004), manufacturer specifications or customer specifications.

MS Mild Steel OR Other/Unknown Check with your local state agency for certification of compliance on Legal-for-Trade items. The weight accuracy class is referenced in the Description of Weights. Unless otherwise noted, the weights calibrated meet the requirements of the accuracy class. Results relate only to weights calibrated. The Surface Finishes of weights are evaluated visually. Weights are screened for magnetism using work instruction WI05-0035 when they are new, when requested by the customer or when weights are suspected of not meeting specifications. Density if measured is measured using OIML R111-1 (2004) method A2. Conventional Mass is reported based on a reference density of 8.0 g/cm3. The Uncertainty of Measurement is included in the determination of Maximum Permissible Error (MPE) Pass/Fail Criteria. The specifications for Maximum Permissible Error (MPE) can be found in NIST Handbook 105-1

A Dusted with brush or cloth Spot cleaned with ethyl alcohol

No cleaning performed

Aluminum

Cast Iron

Iron

Stainless Steel

Full surface cleaned with ethyl alcohol

С

AL

SS

CI

IR

The Uncertainty assigned to the Conventional Mass values are the result of the root-sum-square of the type A and type B components, calculated in accordance with NIST SOP 29 and the Guide to the expression of uncertainty in measurement, with coverage factor (k=2), to express the expanded uncertainty with an approximate 95.45% confidence level. This report is not to be used to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any government agency. This document and all data within, shall not be reproduced, except in full, without the written approval of Rice Lake Weighing Systems.



Prepared By:

Rice Lake Weighing Systems®●PN 64784●12/21 230 West Coleman Street ● Rice Lake, WI 54868 ● USA

TEL: 715-234-9171 FAX: 715-234-6967

Definitions: http://certs.ricelake.com/certs/DefinitionsV2.docx

Page 1 of 2

23 Feb 2022

Issued Date:





RICE LAKE

Certificate of Weight Calibration

ISO/IEC 17025 & ANSI/NCSL-Z540-1-1994 ACCREDITED

Traceable Certificate Number: 3330900A Temperature Range: 21.79 °C to 22.21 °C

Client: ADVANCED SCALE INC Pressure Range: 737.62 mmHg to 744.28 mmHg

Date Calibrated: 22 Feb 2022 to 23 Feb 2022 Relative Humidity Range: 48 % to 51 %

As Left Data (As Found Data is undifferentiated from As Left Data unless listed in As Found Data table)															
Nominal Value	Unique ID	True Mass (Same UOM as Nom.)	True Mass Corr. (mg)	Conv. Mass (Same UOM as Nom.)	Conv. Mass Corr. (mg)	(<i>k</i> =2) Unc. (± mg)	MPE (± mg)	MPE Pass (Y=Pass N=Fail)	Assumed Density (g/cm ³)	Assumed Material	Const. Type	Balance Used	Reference Standard Set Used	Density	Clean Level
5 mg	0M31	5.00250	0.00250	5.00249	0.00249	0.00095	0.010	Υ	7.95	SS	I	503Q	L595Q	1.1658	8 A
20 mg	0M31	20.00019	0.00019	20.00017	0.00017	0.00085	0.010	Υ	7.95	SS	I	503Q	L595Q	1.1656	6 A
200 mg	0M31	200.00197	0.00197	200.00178	0.00178	0.00083	0.010	Υ	7.95	SS	I	2022Q	L595Q	1.1561	Α
200 mg	0M31.	199.99807	-0.00193	199.99788	-0.00212	0.00083	0.010	Υ	7.95	SS	I	2022Q	L595Q	1.1561	Α
500 mg	0M31	500.0014	0.0014	500.0010	0.0010	0.0010	0.010	Υ	7.95	SS	I	2022Q	L595Q	1.1561	Α
1 g	0M31	1.0000121	0.0121	1.0000111	0.0111	0.0013	0.034	Υ	7.95	SS	I	2022Q	L595Q	1.1561	Α
2 g	0M31	2.0000015	0.0015	1.9999996	-0.0004	0.0015	0.034	Υ	7.95	SS	II	2022Q	L595Q	1.1561	Α
2 g	0M31.	2.0000137	0.0137	2.0000118	0.0118	0.0015	0.034	Υ	7.95	SS	II	2022Q	L595Q	1.1561	Α
5 g	0M31	4.9999766	-0.0234	4.9999719	-0.0281	0.0033	0.034	Υ	7.95	SS	II	2022Q	L595Q	1.1561	Α
10 g	0M31	10.0000206	0.0206	10.0000112	0.0112	0.0093	0.050	Υ	7.95	SS	II	1958Q	L595Q	1.1657	' A
20 g	0M31	20.0000218	0.0218	20.0000029	0.0029	0.0060	0.074	Υ	7.95	SS	II	1958Q	L595Q	1.1648	Α
20 g	0M31.	20.0000108	0.0108	19.9999919	-0.0081	0.0060	0.074	Υ	7.95	SS	II	1958Q	L595Q	1.1655	, A
50 g	0M31	50.000109	0.109	50.000061	0.061	0.010	0.12	Υ	7.95	SS	II	1958Q	L595Q	1.1656	Α
100 g	0M31	99.999919	-0.081	99.999825	-0.175	0.020	0.25	Υ	7.95	SS	II	1958Q	L595Q	1.1660) A

As Found Data															
Nominal Value	Unique ID	True Mass (Same UOM as Nom.)		Conv. Mass (Same UOM as Nom.)	Conv. Mass Corr. (mg)	(<i>k</i> =2) Unc. (± mg)	MPE (± mg)	MPE Pass (Y=Pass N=Fail)	Assumed Density (g/cm ³)	Assumed Material	Const. Type	Balance Used	Reference Standard Set Used	Air Density (mg/cm ³)	Clean Level
50 g 0M31		49.999924	-0.076	49.999876	-0.124	0.010	0.12	NX	7.95	SS	II	1958Q	L595Q	1.1659) A