Certificate of Weight Calibration

ISO/IEC 17025:2017 & ANSI/NCSL-Z540-1-1994 ACCREDITED

		ISO/I	IEC 17025:2017 & ANS	I/NCSL-	2540-1-1994 ACCREDITED					
Traceable Certificate Number:				-						
Contractor:	ADVANCED SCALE INC	/	the Nati	onal Institute of						
	13 DELTA DR UNIT 6		1	N.	Se la					
	LONDONDERRY, NH 03053									
	10-01		5	Λ						
Purchase Order Number:	10584		1 the second sec							
Client:										
	13 DELTA DR UNIT 6		eable to the Silling							
	LONDONDERRY, NH 03053		and the second s		000					
Date Received:	25 Feb 2025		1 B							
Date Calibrated:	Calibrated: 27 Feb 2025 to 01 Mar 2025				EIGHING SYSTE					
Recalibration Date:	28 Feb 2026			-W	EIGHING					
NIST Certificate Number:	684/O-0000046697									
If there are two NIST numbers, one or bot	h may apply									
Calibrated By:	05, 17									
	Procedure: WI05-0095 Rev. E									
•	Condition of Weights: Acceptable for Calibration									
Description of Weights:	5 mg to 100 g Polished Weights, ASTM Class 1, S/I	N 0M31	1							
Comments:	Kan Nataa	Cleaning Levels								
	Key Notes	A 1			eveis					
	eight does not meet the finish requirements	A Dusted with brush or cloth B Spot cleaned with ethyl alcohol								
4	Indicates the weight does not meet the material requirements		C Full surface cleaned with ethyl alcohol							
New Wt 💎 Indicates new	weight	D Spot cleaned with non-alcohol solvent followed by ethyl alcohol								
Missing Wt 🛛 📥 Indicates repla	ced missing weight with new weight	E Full surface cleaned with non-alcohol solvent followed by ethyl alcohol								
Damaged Wt 🛛 📉 Indicates repla	naged Wt 🛛 🔀 Indicates replaced damaged weight				, ,					
	ced out of tolerance weight	Material Abbreviations								
	ction plus or minus Uncertainty greater than or equal to MPE	AL	Aluminum	TA	Tantalum					
	ced magnetic weight	SS	Stainless Steel	BR	Brass					
Design Indicates the w	n Indicates the weight does not meet the design or shape requirements				Platinum					
Repainted Indicates the w	eight was repainted after As Found obtained	IR	Iron	NS	Nickel Silver					
Other Φ See comments	s above	MS	Mild Steel	OR	Other/Unknown					

Check with your local state agency for certification of compliance on Legal-for-Trade items. The weight accuracy class is referenced in the Description of Weights. Unless otherwise noted, the weights calibrated meet the requirements of the accuracy class. Results relate only to weights calibrated. The Surface Finishes of weights are evaluated visually. Weights are screened for magnetism using work instruction W105-0035 when they are new, when requested by the customer or when weights are suspected of not meeting specifications. Density if measured using OIML R111-1 (2004) method A2. Conventional Mass is reported based on a reference density of 8.0 g/cm³. The Uncertainty of Measurement is included in the determination of Maximum Permissible Error (MPE) Pass/Fail Criteria. The specifications for Maximum Permissible Error (MPE) can be found in NIST Handbook 105-1 (2019), NIST Handbook 105-1 (1990), ASTM E617-23 or OIML R111-1 (2004), manufacturer specifications or customer specifications.

The Uncertainty assigned to the Conventional Mass values are the result of the root-sum-square of the type A and type B components, calculated in accordance with NIST SOP 29 and the Guide to the expression of uncertainty in measurement, with coverage factor (*k*=2), to express the expanded uncertainty with an approximate 95.45% confidence level. This report is not to be used to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any government agency. **This document and all data within, shall not be reproduced, except in full, without the written approval of Rice Lake Weighing Systems**.



RICE LAKE



Prepared By: **Rice Lake Weighing Systems®**●PN 64784●1/24 230 West Coleman Street●Rice Lake, WI 54868●USA TEL: 715-234-9171●FAX: 715-234-6967 Definitions: http://certs.ricelake.com/certs/DefinitionsV2.docx Page 1 of 2 03 Mar 2025

Issued Date:



RICE LAKE Certificate of Weight Calibration

Traceable Certificate Number: 3836862 Client: ADVANCED SCALE INC Date Calibrated: 27 Feb 2025 to 01 Mar 2025 As Left Data (As Found Data is undifferentiated from As Left									ISO/IEC 17025:2017 & ANSI/NCSL-Z540-1-1994 ACCREE Temperature Range: 21.43 °C to 21.54 °C Pressure Range: 714.62 mmHg to 737.33 mmHg Relative Humidity Range: 49 % to 55 % ft Data unless listed in As Found Data table)							
Nominal Value	Unique ID	True Mass (Same UOM as Nom.)	True Mass Corr. (mg)	Conv. Mass	Conv. Mass Corr. (mg)	(<i>k</i> =2) Unc. (± mg)	MPE (± mg)	MPE Pass (Y=Pass N=Fail)	Assumed Density (g/cm ³)	Assumed Material	Const. Type	Balance Used	Reference Standard Set Used	Air Density (mg/cm ³)	Clean Level	
5 mg		5.00267	0.00267	5.00266		0.00085	0.010		7.95		I	503Q				
20 mg		20.0006	0.0006	20.0006		0.0011	0.010		7.95		I	503Q				
200 mg		200.00202	0.00202	200.00183		0.00060	0.010		7.95		I	2022Q		-		
200 mg		199.99833	-0.00167	199.99814	-0.00186	0.00060	0.010	Y	7.95		I	2022Q	L595Q	1.1425	5 A	
500 mg	0M31	499.99963	-0.00037	499.99916	-0.00084	0.00078	0.010	Y	7.95	SS	I	2022Q	L595Q	1.1425	5 A	
1 g	0M31	1.0000102	0.0102	1.0000092	0.0092	0.0011	0.034	Y	7.95	SS	I	2022Q	L595Q	1.1425	5 A	
2 g	0M31	1.9999992	-0.0008	1.9999974	-0.0026	0.0013	0.034	Y	7.95	SS	П	2022Q	L595Q	1.1425	5 A	
2 g	0M31.	2.0000047	0.0047	2.0000028	0.0028	0.0013	0.034	Y	7.95	SS	П	2022Q	L595Q	1.1425	5 A	
5 g	0M31	5.0000159	0.0159	5.0000112	0.0112	0.0029	0.034	Y	7.95	SS	П	2022Q	L595Q	1.1425	5 A	
10 g	0M31	9.9999855	-0.0145	9.9999760	-0.0240	0.0057	0.050	Y	7.95	SS	П	2060Q	L595Q	1.1208	3 A	
20 g	0M31	19.9999879	-0.0121	19.9999690	-0.0310	0.0057	0.074	Y	7.95	SS	П	2060Q	L595Q	1.1208	3 A	
-	0M31.	19.9999724	-0.0276	19.9999535	-0.0465	0.0057	0.074	Y	7.95	SS	П	2060Q	L595Q	1.1208	3 A	
50 g	0M31	50.0001218	0.1218	50.0000746	0.0746	0.0087	0.12	Y	7.95	SS	П	2060Q	L595Q	1.1564	A	
100 g		100.000018	0.018	99.999923	-0.077	0.019	0.25	Y	7.95	SS	П	2060Q	L595Q	1.1208	3 A	

As Found Data															
Nominal Value	Unique ID	True Mass (Same UOM as Nom.)	True Mass Corr. (mg)	Conv. Mass (Same UOM as Nom.)	Conv. Mass Corr. (mg)	(<i>k</i> =2) Unc. (± mg)	MPE (± mg)	MPE Pass (Y=Pass N=Fail)	Assumed Density (g/cm ³)	Assumed Material	Const. Type	Balance Used	Reference Standard Set Used	Air Density (mg/cm ³)	Clean Level
50 g	0M31	49.9999112	-0.0888	49.9998640	-0.1360	0.0087	0.12	ΝX	7.95	SS	II	2060Q	L595Q	1.1208	3 A